

**PRODUCT PROFILE****DECK-PATCH****TUFF SYSTEM ADVANTAGE**

Tuff Industries Deck-Patch is an industry leading, fast drying, all-purpose smoothing compound used on both plywood and concrete deck surfaces. Before installing Tuff waterproof vinyl decking use our Deck-Patch to cover and smooth out minor imperfections, knot holes, T&G joints, voids, and de-lamination.

Tuff Industries Deck-Patch is a cement based formula, which allows for the installation of Tuff waterproof vinyl decking within 20 minutes after application on absorbent substrates. Our unique compound utilizes very fine aggregates enabling it to be applied by trowel from a true featheredge up to 1" (25 mm) depth in a single application while maintaining superior bond properties.

For additional information, specifications, CAD drawings or MSDS, please contact  
Tuff Industries Inc. **Toll Free: 1-877-860-9333**

**NOTES:** This document is not an installation guideline. Tuff Industries Inc. will not be responsible for the improper use or installation of its products.

**FEATURES**

- Fine aggregate with fast dry formula
- Smooth surface finish with minimal substrate preparation
- Superior bond with excellent absorbency
- No surface primer required

**TECHNICAL NOTES**

- Working temperature: Min 50F (10C)
- Working time: Approx. 20 minutes
- Application thickness: Featheredge to 1"
- Mix ratio: 2 parts water to 1 part powder

**PACKAGING**

- Single Pails : 5 lb. / 2.27kg
- Single Pails : 10lb. / 4.54kg

