

PRODUCT PROFILE

LOW VOC CONTACT ADHESIVE



TUFF SYSTEM ADVANTAGE

Low VOC Contact Adhesive is designed specifically for use with Tuff vinyl membrane systems providing exceptional bond strength on both flat and vertical surfaces.

For additional information, specifications, CAD drawings or MSDS, please contact Tuff Industries Inc.

Toll Free: 1-877-860-9333

NOTES: This document is not an installation guideline.

Tuff Industries Inc. will not be responsible for the improper use or installation of its products.

FEATURES

- Low VOC solvent based adhesive
- For use on flat and vertical surfaces
- Fast curing
- Minimal plasticizer impact
- Compatible with all Tuff membranes

TECHNICAL NOTES

- Apply at temperatures at or above 40°F / 4°C and rising
- Coverage: 50-70 sq. ft. / gal
- Stir adhesive before applying
- Do not freeze
- Frozen adhesive must be discarded

PACKAGING

- 1 x 5 US gal / 18.9 L
- Skid – 48 pails x 5 US gal / 18.9 L



TUFDEK

ECONODEK

TUFF-SHIELD

TUFF INDUSTRIES
INCORPORATED

www.tufdek.com | www.econodek.com | www.tuff-shield.com | 1.877.860.9333